

888-273-7077

sales@fibertexandsupply.com

Safely guide suspended loads or reach for tag lines and rigging. Each SHT3 is enhanced with a Carbon Fiber sleeve on the neck where the tooling head is mounted. This increases the tool's strength significantly. The tapped end of our type 3 tool's internally threaded plug enables the use of our lap link and other specialty tools with the original push/pull head.

- Push/Pull Hooks on Y-head
- Graphite Reinforced Head Joint
- Extreme Temperature Durable Head
- Reflective Tape
- Safety Yellow Fiberglass Reinforced Pipe
- Large Protective Hand Grip
- Reflective Label



Tapped End Plug



Lap Link Tool



Large Protective Grip

| MODEL | DESCRIPTION | OVERALL LENGTH | WEIGHT |
|---------|----------------------------------|----------------|---------|
| SHT3-42 | 42" Tapped handle push/pull tool | 37-1/4" | 2.5lbs |
| SHT3-50 | 50" Tapped handle push/pull tool | 45-1/2" | 2.75lbs |
| SHT3-72 | 72" Tapped handle push/pull tool | 81" | 4lbs |

Site specific solutions available on request. **Ratings:** Load Testing - Static Pull = 400 lbs. / Compression = 600 lbs. Our tools are not lifting/load bearing tools, SWL cert not required. Major components tested to ASTM standards. Seeking NOPS (AU) Review. **Made in USA.**

